

**MONOCURE WB**  
**Method Statement**  
**(Water based paraffin dispersion concrete curing compound)**

**SECTION A**

**GENERAL COMMENT**

**High temperature working**

(i) Store materials in a cool place and away from direct sunlight.

(ii) Store materials in warm place during winter time to avoid freezing.

**Equipment**

It is suggested that the following list of equipment is adopted as a minimum requirement:

**Protective clothing** : protective overalls  
Good quality gloves, goggles and face mask

**Mixing equipment** : Spray equipment 20 litre or more

**SECTION B**

**APPLICATION**

**1.0 Surface Preparation**

1.1 Always mix material well every time before use.

1.2 Fresh concrete surfaces should be free from water bleeding or any standing water prior to curing compound application.

**2.0 Application**

**2.1 Fresh Concrete:**

2.1.1 Immediately and once concrete surface finish is complete, spray **MONOCURE WB**, while it is green.

2.1.2 The spray nozzle should be held approximately 450 mm from concrete surfaces and passed back and forth to ensure complete coverage.

The recommended coverage rate should be around 3 m<sup>2</sup>/litre. Pump pressure should be maintained all the time to give even, fine spray.

2.1.3 The applied film should be protected for at least 3 hours from rain.

**2.2 Dry Concrete before Shutter de-molding:**

2.2.1 Immediately after de-shuttering, concrete surfaces should be moist with clean water.

2.2.2. After moisting, spray **MONOCURE WB** and at even spray back and forth to ensure complete coverage at a rate of 3 m<sup>2</sup>/litre.

**3.0 Cleaning**

3.1 Tools and equipment (especially spraying nozzle) should be cleaned with plenty of water.

## SECTION C

### APPROVAL AND VARIATIONS

This method statement is offered by STARKE as a '**standard proposal**' for the application of Stare Construction Chemicals.

It remains the responsibility of the Engineer to determine the correct method for any given application. Where alternative methods are to be used, these must be submitted to STARKE for approval, in writing, prior to commencement of any work.

STARKE will not accept responsibility or liability for variations to the above method statement under any other condition.



**Starke Polymer Ltd**  
Plot 158, kampala uganda

Tel + 256 787 288 087  
Tel + 256 708 693 991

Email: [info@starkepolymers.com](mailto:info@starkepolymers.com)  
[www.Starkepolymers.com](http://www.Starkepolymers.com)